

# TRX8000

TREADMILL



## TECHNICAL DATA

Speed	1 to 20 km/h
Incline	0 to 15%
Heart rate	Contact & Telemetric
Drive motor	3,00 HP AC Drive - 5,00 HP (peak) w/ Grade H Insulation
Deck	25 mm Phenolic, Reversible, Double-Sided, Wax-Coated
Deck width	580 mm
Belt dimensions	560 x 1550 mm Habasit® Commercial, Multi-Ply
Rollers	76 mm - balanced
Cushioning	6 Cushions (rear rigid mount)
Handrails	Stout, Short Lateral Dipped Tubing
Frame	Heavy-Gauge High-Strength Steel w/ durable Powder-Coat Paint, Aluminum Console Masts - 80% preassembled
Unique features	2 Motor Cooling Fans, Console Cooling Fan, Grade H Insulation Drive Motor, Fit Test (Gerkin Protocol), Heart Rate % Profile, Dual Water Bottle Holders
Weight/Gross weight	160 Kg / 190 Kg
Set up size	2140 x 890 x 1450 mm (L x l x h)
Packing size	2260 x 920 x 540 mm (L x l x h)
Max user weight	190 Kg
Compliacens	CE-ROHS-EN957 SA (Studio High Accuracy)

## CONSOLE

### Console:

Large Blue-LED 145x60 mm Matrix Window  
w/ 20-Character Message Center,  
and 4 Separate LED Windows,  
Heart Rate % Profile,  
Integrated Reading Rack

### Console Feedback:

Time, Distance, Calories, Pace, Speed, Incline,  
Pulse, METs

### Programs:

10: Manual, Hill, Fat Burn, Cardio, 5K Run,  
Interval, Custom, Fit Test (Gerkin Protocol),  
2 Heart Rate